


Universe	Operators
Type	Verticality
Category	Pulleys
Subcategory	Adventure park pulleys



TRAC CLUB

TRAC CLUB is an easy-to-use trolley designed for adventure parks. It is ergonomic, with excellent grip, and allows the client to install the trolley on the cable with one hand. The ends are equipped with protective impact surfaces to reduce the risk of pinched fingers, and with two connector support grooves to avoid abrasion by the cable. The JOKO and AVENTEX lanyards are directly integrated in the trolley, so the unit cannot be separated or lost. Product life is extended thanks to extremely durable bearings and removable impact surfaces available as spare parts.



The ergonomic opening system allows the client to easily install the trolley on the cable with one hand.



Excellent grip makes it comfortable for the client to manipulate.



Two positioning support grooves for the connectors limit abrasion by the cable.



The trolley connects easily to the harness, thanks to the CARITRAC stowage accessory.

Short Description Durable, easy-to-use trolley for adventure parks

Selling Points

- Easy-to-use trolley designed for adventure parks:
 - ergonomic opening system allows the client to easily install the trolley on the cable with one hand
 - two aligned sheaves guarantee excellent stability on the zip line
 - ergonomic lower section provides a comfortable grip for the client
 - front and rear impact surfaces limit the risk of pinched fingers
 - two positioning support grooves for the connectors limit abrasion by the cable
 - JOKO or AVENTEX lanyards are directly integrated in the trolley, so the trolley/lanyard unit cannot be separated or lost
 - easy connection to the harness, thanks to the CARITRAC stowage accessory.
- Excellent durability for easy maintenance and extended product life:
 - single-row ball-bearings offer excellent durability
 - protective impact surfaces are removable and available as replacement parts to extend the life of the trolley
- Available individually or in pack of five

Specification

- Cable diameter: 9 to 13 mm (may also be used on ropes)
 - Weight per unit: 455g
 - Material(s): aluminum frame, stainless steel sheave, nylon
 - Certification(s): CE EN 17109, CE EN 12278, UIAA
 - Maximum speed: 25 m/s
 - Recommended zip line length: up to xxx m
-

Specifications by reference

Reference(s)	P023AB00	P023AB01
	sold individually	sold by pack of 5
Made in	FR	FR
Guarantee	3 years	3 years
Inner pack count	1	1
Case quantity	5	1
EAN	3342540837119	3342540837126

Spare part(s) Impact surfaces for TRAC trolleys

Accessory(ies) CARITRAC